

TWO-IN-ONE LADDER



- Oval steps prevent discomfort as caused by round rungs and allow greater productivity
- Latch allows double lock in straight mode; hinge provides safe locking in A-mode
- Smooth edged finishing prevents bodily harm
- Facilitates access to heights when in straight mode or offers ability to carry out work in A-mode



Note: Following sizes are not extendable into straight mode

- TIO 3
- TIO 4
- TIO 12

TWO-IN-ONE LADDER								
LOAD CAPACITY: 150 KG								
ITEM CODE	STEPS	APPROX STILE LENGTH		A MODE HEIGHT		EXTENDED HEIGHT		APPROX WEIGHT
		METRES	FEET	METRES	FEET	METRES	FEET	KILOGRAMS
TIO 3	3	0.9	3'	0.7	2'4"	—	—	3.3
TIO 4	4	1.2	4'	1.0	3'3"	—	—	4.4
TIO 5	5	1.5–2.6	5' to 8'6"	1.3	4'3"	2.2	7'3"	5.5
TIO 6	6	1.8–3.2	6' to 10'6"	1.6	5'3"	2.8	9'2"	6.6
TIO 7	7	2.1–3.8	7' to 12'6"	1.9	6'3"	3.4	11'2"	7.8
TIO 8	8	2.4–4.4	8' to 14'5"	2.2	7'3"	3.9	12'10"	8.9
TIO 9	9	2.7–5.1	9' to 16'9"	2.5	8'3"	4.5	14'9"	10.1
TIO 10	10	3.0–5.6	10' to 18'4"	2.8	9'2"	5.0	16'5"	11.4
TIO 12	12	3.6	12'	3.3	10'10"	—	—	13.8

TECHNICAL FEATURES ARE INDICATIVE AND CAN BE MODIFIED WITHOUT PRIOR NOTICE
THE NUMBER OF STEPS MENTIONED INCLUDES THE TOP STEP, ALTHOUGH ONE MUST NOT STAND/WORK ON THIS STEP

Generally used when straight access or as A-type long duration works are required:

Construction

Stores

DIY

TAKING YOU ONE STEP HIGHER