

FULL FIBREGLASS LADDER



- Fibre step construction not only provides great load bearing capacity, serration also ensures good grip
- Fibreglass box profiles channels provide greater load capacity than C-channel variations
- Optional rubber shoes with anti-slip function
- Materials are resistant to electricity, temperature variations and corrosion
- **Optional GI/SS brackets to fix to walls, for vertical access**



FULL FIBREGLASS LADDER				
LOAD CAPACITY: 150 KG				
ITEM CODE	STEPS	APPROXIMATE HEIGHT		APPROXIMATE WEIGHT
		METRES	FEET	KILOGRAMS
FFL 6	6	2.1	6'11"	5.0
FFL 7	7	2.4	7'10"	5.8
FFL 8	8	2.7	8'10"	6.5
FFL 12	12	3.9	12'10"	9.5
FFL 13	13	4.2	13'9"	10.2
FFL 15	15	4.8	15'9"	11.7
FFL 17	17	5.7	18'9"	13.2
FFL 19	19	6.0	19'8"	14.7

TECHNICAL FEATURES ARE INDICATIVE AND CAN BE MODIFIED WITHOUT PRIOR NOTICE

Applicable for:

Zone 1 Environments in Oil & Gas Industries

Pharmaceutical & Medical Industries

Sewerage

TAKING YOU ONE STEP HIGHER